

SGC Technologies, Inc.

PRODUCT SPECIFICATION FOR INFORMATION

PRODUCT NAME: SDPX-8R8-TYPE


PART NO: SDPX-2150-8R8-1960BP40B

Center frequency	1960 MHz	2150 MHz
Pole	4	4
Bandwidth(BW)	Fo ±20 MHz	Fo ±20 MHz
Insertion Loss	2.0dB max	2.0 dB max
VSWR in BW	1.5 max	1.5 max
Ripple in BW	0.5 dB max	0.5 dB max
Attenuation	50dB min at 2130MHz - 2170MHz	50dB min at 1940MHz - 1980MHz
In/Out Impedance	50 ohm	50 ohm

NOTE:


EQUIPMENT used :HP 8753D

DIMENSION:



SDPX-2150-8R8-1960BP40B

CH1 S₁₁ Log MAG 5 dB/ REF 0 dB 3: -25.965 dB
 CH2 S₂₁ Log MAG 10 dB/ REF 0 dB 3: -1.2733 dB




CENTER 2 055.000 000 MHz

SPAN 400.000 000 MHz

6 Nov 2002 14:29:57

CH1 S₂₂ Log MAG 5 dB/ REF 0 dB 2: -21.252 dB
 CH2 S₂₁ Log MAG 10 dB/ REF 0 dB 2: -1.8873 dB



CENTER 2 055.000 000 MHz

SPAN 400.000 000 MHz /